



Construction and Energy Costs for Radiant System in California Bay Area

Symposium: Optimizing Radiant Systems

Oct 23, 2019

INTEGRATED

[RESILIENT]

SUSTAINABLE

Acknowledgements



- This work was done when the presenter worked at Taylor Engineering with support from Hwakong Cheng and Steve Taylor
- This study was funded by California Energy Commission Electric Program Investment Charge (EPIC) under the Optimizing Radiant Systems for Energy Efficiency and Comfort project, led by Center for the Built Environment at UC Berkeley

Agenda



- **Project overview**
- **Case study building**
- **Cost data**
- **How to reduce construction costs**
- **Energy performance**
- **How to reduce energy costs**

Project Overview



Objectives

- § Provide cost data for radiant systems in California Bay Area
- § **Suggest opportunities to reduce cost and improve energy efficiency**

Approach

- § Provide baseline and alternative design options
- § Cost estimation by contractors
- § Energy performance evaluation by EnergyPlus

Background



Status of VAV

- § Predominant HVAC approach
 - Optimized construction process
 - Competitive market
- § Design guidelines
 - Advanced VAV System Design Guide
 - ASHRAE Guideline 36



Image: an online map of radiant system buildings

Status of radiant

- § Small market share, mostly in low-energy and ZNE projects
- § Limited design guidelines and tools
- § Lack of familiarity by building construction industry

Case study building



Real building with radiant design

Simplified floor plan

- § Open office with meeting rooms
- § Total floor area 112,000 ft²

Building features

- § Solar load control
 - Window-wall ratio 40%
 - Glazing U-value 0.4 and SHGC 0.28
 - Exterior overhang
- § LED lights and daylight control
- § Advanced plug load control






Image: EnergyPlus model of the case building

Radiant slab design



- High thermal mass radiant system with tubes in every ceiling slab
- 10 radiant zones per typical floor
- 13 DOAS VAV zones per typical floor
 - Demand controlled ventilation in large conference rooms



- Cooling-only Zones
- Cooling/Heating Zones

Radiant slab zoning plan (part of typical floor)



- Large Conference Rooms
- Open Office

DOAS zoning plan (part of typical floor)

Radiant system design




Dedicated outdoor air system (DOAS)

- § Design air flowrate
19,400 cfm
- § Changeover
heating/cooling coil

Central plant

- § Four-pipe air source
heat pump
- § Serves both DOAS and
radiant slabs to reduce
cost



Radiant design schematic

Construction costs



HVAC and controls only


Common mechanical elements
NOT included

San Mateo labor rate


- Sheet metal: \$123/hr
- Piping: \$118/hr

Results

§ Average : \$38.9/ft²



Construction cost breakdown




Piping labor breakdown



Radiant slab: \$6.6/ ft²

Floor distribution + risers: \$2.9/ ft²




Equipment Cost



Radiant equipment: \$2.82/ ft²

DOAS AHU : \$0.79/ ft²


ASHP: \$2.71/ ft²



Impact of labor rate



- National average labor rate: \$85/hr



**How to reduce radiant
system cost?**

Facilitate the use of radiant mat



Costs

§ Mats : ~\$4 - 6 /ft²

§ Loops*: ~\$6 - 8 /ft²



Radiant roll-out mat

Limitations for mats

§ Maybe limited by shape and size of radiant zones

§ May not be cost effective for smaller jobs (assembled on a made-to-order basis)




Traditional loops

* For 6-inch tube spacing

Hydronic distribution layout: Multiple risers vs. single riser



- § Strategically locate risers to minimize piping: 30% piping reduction
- § Cost savings: \$2.5/ft²



Single riser: Typical floor piping layout



Multiple risers: Typical floor piping layout

Use larger radiant tube spacing: 9” vs. 6 in”



- § Loop design: ~\$1.7/ft² of labor cost savings
- § Mat design : 5-15% cost savings and 5% labor savings
- § Thermal capacity: initial evaluation shows similar dynamic performance

Other approaches to reduce radiant costs



- § Large vs. small radiant zones
- § Consider no radiant tubes in ground or roof slab
- § Use passive supplemental system strategically (For example, ceiling fans)
- § Hydronic system type: 4-pipe vs. 2-pipe vs. mixed 4 and 2-pipes
- § Reduce central plant equipment size with load shifting
- § More details in the report*

*Feng, J., & Cheng, H. (2018). *Comparison of Construction and Energy Costs for Radiant vs. VAV Systems in the California Bay Area*. Deliverable for California Energy Commission Project EPIC -14-009, Taylor Engineering. Retrieved from <https://escholarship.org/uc/item/13h9z4gg>


HVAC annual site electricity



Total: 2.9 kBtu/ft²

§ Cooling is 41% of total energy


§ Fan energy is 34% of total energy



Central plant cooling and heating load




- Cooling energy use in winter months
- DOAS uses significant energy




**How to reduce radiant
system energy cost?**

Potential for economizer to reduce cooling energy




Implement load shifting strategy to reduce demand



← Radiant slab operates 6 am - 6 pm


Radiant slab operates 0 am-12 pm →




Implement load shifting strategy to reduce demand



- Whole building electricity cost
- High performance design to minimize heat gain is key



Optimize DOAS supply air temperature control





Neutral SAT

OA reset




Large deadband



Optimize DOAS supply air temperature control



- § Use large heating/cooling setpoint deadband
- § Reset supply air temperature higher with space humidity feedback



Approaches to reduce energy cost



- § Take advantage of free cooling with waterside economizer (mild weather in particular)
- § Implement load shifting strategy to reduce demand charge and equipment size
- § DOAS design and control are critical
 - DOAS supply air temperature control is IMPORTANT
 - Avoid unnecessary oversizing of DOAS by strategically distributing the ventilation air
 - Decouple cooling source for radiant slab and DOAS in humid climates
- § More details in the report*

There are opportunities for improving current practice!

*Feng, J., & Cheng, H. (2018). *Comparison of Construction and Energy Costs for Radiant vs. VAV Systems in the California Bay Area*. Deliverable for California Energy Commission Project EPIC -14-009, Taylor Engineering. Retrieved from <https://escholarship.org/uc/item/13h9z4gg>

Questions?





Thank You

Jingjuan (Dove) Feng
jfeng@trccompanies.com